

# XS LO35

## XS TRACK

A functional and attractive spotlight can satisfy different lighting requirements, with minimalistic and compact structure design.



## XS TRACK M19A/M19O/M19T/M19E



XS LO35

10.004A01000


Power	4.5W
Beam angle	13°/20°/28°/60°
Color temperature	2700K/3000K/3500K/4000K
Light efficiency	66lm/W
Color rendering index	≥90
Operating temperature	-25°C - 50°C
Rated life hours	35,000-50,000h LM80
LED chip	COB

CE CB TÜV



### OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □

MATERIAL | AL

# XS LO30

## XS TRACK

The micro spotlight is specially designed for accent lighting, its mini structure allows it to be installed in a small space without being obtrusive.

## XS TRACK M19A/M19O/M19T/M19E



XS LO30


10.005A01000

Power	5.3W
Beam angle	25°/31°/42°/56°
Color temperature	2700K/3000K/3500K/4000K
Light efficiency	87lm/W
Color rendering index	≥90
Operating temperature	-25°C - 50°C
Rated life hours	35,000-50,000h LM80
LED chip	COB



### OPTIONS

1	Non-DIM
---	---------



COLOUR | BK ■ WH □

MATERIAL | AL