



CONE

MINI TRACK M26A/M26T/M26R/M26E



CONE

07.036A01000

Power	20W
Beam angle	18°/25°/36°/60°
Color temperature	2700K/3000K/3500K/4000K/2700K-6000K
Light efficiency	104lm/W
Color rendering index	≥90
Operating temperature	-25°C - 50°C
Rated life hours	35,000-50,000h LM80
LED chip	COB



OPTIONS

1	Non-DIM
2	0/1-10V
3	DALI
4	BLE
5	ZIGBEE

FEATURES



inset single control via
KC BLE Mesh app

07.036A01000



COLOUR | BK+GD BK+WH | MATERIAL | AL

GYRO



Simple design, interesting light, decorating the space, at the same time, creating warm atmosphere.

MINI TRACK M26A/M26T/M26R/M26E



GYRO

07.043A01000

Power	8W
Beam angle	19°/23°/31°
Color temperature	2700K/3000K/3500K/4000K/2700K-6000K
Light efficiency	56lm/W
Color rendering index	≥90
Operating temperature	-25°C - 50°C
Rated life hours	35,000-50,000h LM80
LED chip	COB



OPTIONS

1	Non-DIM
2	0/1-10V
3	DALI
4	BLE
5	ZIGBEE

FEATURES



inset single control via
KC BLE Mesh app

07.043A01000



COLOUR | BK ■ WH □ BR ■ | MATERIAL | AL